




SHIELD

CASEMENT WINDOWS



SHIELD

CASEMENT WINDOWS

Strength & Warmth

The Shield window range from Newark Glass forms part of the company's comprehensive range of PVC-U windows & doors, all designed to meet the demands of UK householders and to withstand the unique British climate. All feature multi-chambered construction for great strength and superb sound and thermal insulation properties.

The PVC-U profile used by Newark Glass in Shield windows has a 70mm outer frame depth, thick walls for great strength and a pleasing contour to the edges - which can be supplied as either a straight bevel or a curved edge.

The Shield range comprises strong and stylish windows, combining a tough frame with espagnolette locking, and where required toughened glass and reinforcing. It also shares one characteristic with all our ranges - excellent thermal insulation - improved

further by the use of Pilkington K Glass which reflects heat back into a room.


Available in white, cherrywood, light oak or mahogany woodgrain PVC-U, Newark Glass' casement windows feature side-hung or top-hung vents, optionally combined with direct glazed fixed lights, and the vents can even be fitted with easy-clean hinges allowing access to the outside. Also, where Building Regulations demand it, fire escape hinges will be fitted.

All of this is finished off by the use of top-quality accessories such as handles and trims that compliment the windows, and the availability of matching doors and patio doors.

Shield windows also come as standard with the reassurance of BSI Kitemarks.



WINDOW STYLES



PLUS MANY MORE STYLES AVAILABLE



SCOTIA BEAD OPTION



WHITE FINISH



OVOLO BEAD OPTION




LIGHT OAK FINISH



HORNED SASH OPTION




CHERRYWOOD FINISH



MORE AVAILABLE...



STYLISH LINES



LEADED LIGHTS

SHIELD CASEMENT WINDOWS SPECIFICATION

WINDOW DESIGN

Casement windows provide an extremely versatile range of sizes, shapes and styles to suit customers' needs in both domestic and commercial applications. The range includes either flat or rounded bevels, while transoms and mullions are all thermally welded. Alternative cills and ancillary components broaden the choice even further.

GLAZING

Newark Glass Shield windows are fitted as standard with 28mm square-edged sealed glazing units and are internally beaded for security. Toughened glass is used where required.

To further enhance the window's thermal insulation properties we use Pilkington K Glass that actually reflects heat back into the room.

REINFORCEMENT

The intrinsic strength of the profile is supplemented where necessary by the inclusion of Steel and Aluminium reinforcing in transoms, mullions, opening vents and the outer frame where extra support is desirable.

WEATHERSEALS

Dual weatherseals fitted to all opening vents have excellent weathering characteristics to ensure long-term reliability and consistent performance.

HARDWARE

The hinges, locks and handles used on the Shield range have been chosen to provide the combined benefits of reliable operation, ease of opening, high security when closed and colours to match the window.

The window locks used are high-quality espagnolette locks that use a sliding 'cam' that interlocks into a metal keep..

QUALITY ASSURANCE

Newark Glass is registered to ISO9001:2000 for the manufacture of windows, doors, sealed units and conservatories and employs full-time QA staff including Inspectors and Testers.

FURTHER DETAILS

Details of the full Shield range and our other products are available from any of our offices and on our website:

WWW.NEWARKGLASSGROUP.COM



www.securedbydesign.com



OAK TREE HOUSE, BRUNEL DRIVE
NEWARK, NG24 2EG - 01636 610088
WWW.NEWARKGLASSGROUP.COM

